



NDS-6.0-XXXXK-24

No Dots® Series Rigid LED Bar Low Profile Diffuser Lens



90 CRI
DIMS to 1%



Secondary Wiring Requirements

Windy City Wire Part 007960 or equivalent. Maximum lead distance up to 100 FT from power supply to first LED fixture with Innovative Lighting, Inc Driver. Consult factory for longer leads.

Mounting Recommendations

3M VHB 4910, 3M 230 Sealant. Actual mounting to be determined and provided by customer.

Product Features

Color Rendering Index: 90

Circuit Type: Constant Voltage 24V, Class 2 Power Unit Only, Cuttable in 1.0 IN increments (0, 1, 2, 3.)

Maximum Power Consumption: 6.0 Watts per foot (19.685 per meter)

Beam Angle: 120°

Operating Temperature Range: -4°F to 122°F (-20°C to 50°C)

Dimming: Consistently to 1% with Innovative Lighting, Inc LED Drivers (See LED Driver Information Sheet)

Finish: Heat-Dissipating Aluminum (Custom Colors Available)

Lens: Fire-Resistant Extruded Acrylic (Custom Colors Available)


Color Temperatures:

Lumen Output per FT:
Lumen Output per M:

2700K	3000K	3500K	4000K
187	203	225.3	252.33
613.36	665.84	738.984	827.64

IES File Number:

ITL93150



IC Based Constant Current Regulator with Temperature Compensation Circuits, Lengths from 6.0 IN to 96.0 IN (152.4mm to 2438.4mm), Patent-Licensed LEDs, Total Quality-Controlled Manufacturing Process, Three-Stage Binning System, Suitable for Wet Locations - Use Only with Class 2 Power Unit, Suitable for Cove Lighting, Suitable for Installation in the Storage Area of Clothes Closet, Suitable for Cabinet or Under Cabinet Use



Telephone (972) 721-1177
Innovative-Lighting.com
2324 Hinton Drive, Irving, TX 75061

Published 2020-OCT 01